


MOS Field Effect Transistor 2SK3113

■ Features

- Low on-state resistance
 $R_{DS(on)} = 4.4 \Omega$ MAX. ($V_{GS} = 10 \text{ V}$, $I_D = 1.0 \text{ A}$)
- Low gate charge
 $Q_G = 9 \text{ nC}$ TYP. ($V_{DD} = 450 \text{ V}$, $V_{GS} = 10 \text{ V}$, $I_D = 2.0 \text{ A}$)
- Gate voltage rating $\pm 30 \text{ V}$
- Avalanche capability ratings



■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

| Parameter | Symbol | Rating | Unit |
|-------------------------|------------|------------------------|------------------|
| Drain to source voltage | V_{DSS} | 600 | V |
| Gate to source voltage | V_{GSS} | ± 30 | V |
| Drain current | I_D | ± 2.0 | A |
| | I_{DP}^* | ± 8.0 | A |
| Power dissipation | P_D | $T_c=25^\circ\text{C}$ | 20 |
| | | $T_a=25^\circ\text{C}$ | 1.0 |
| Channel temperature | T_{ch} | 150 | $^\circ\text{C}$ |
| Storage temperature | T_{stg} | -55 to +150 | $^\circ\text{C}$ |

* $PW \leq 10 \mu\text{s}$, Duty Cycle $\leq 1\%$

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

| Parameter | Symbol | Test conditions | Min | Typ | Max | Unit |
|-------------------------------------|---------------|--|-----|-----|----------|---------------|
| Drain cut-off current | I_{DSS} | $V_{DS}=600\text{V}, V_{GS}=0$ | | | 100 | μA |
| Gate leakage current | I_{GSS} | $V_{GS} = \pm 30\text{V}, V_{DS}=0$ | | | ± 10 | μA |
| Gate to source cut off voltage | $V_{GS(off)}$ | $V_{DS}=10\text{V}, I_D=1\text{mA}$ | 2.5 | | 3.5 | V |
| Forward transfer admittance | $ Y_{fs} $ | $V_{DS}=10\text{V}, I_D=1.0\text{A}$ | 0.5 | | | S |
| Drain to source on-state resistance | $R_{DS(on)}$ | $V_{GS}=10\text{V}, I_D=1.0\text{A}$ | | 3.3 | 4.4 | Ω |
| Input capacitance | C_{iss} | $V_{DS}=10\text{V}, V_{GS}=0, f=1\text{MHz}$ | | 260 | | pF |
| Output capacitance | C_{oss} | | | 60 | | pF |
| Reverse transfer capacitance | C_{rss} | | | 5 | | pF |
| Turn-on delay time | t_{on} | $I_D=1.0\text{A}, V_{GS(on)}=10\text{V}, V_{DD}=150\text{V}, R_G=10 \Omega, R_L=10 \Omega$ | | 7 | | ns |
| Rise time | t_r | | | 2 | | ns |
| Turn-off delay time | t_{off} | | | 22 | | ns |
| Fall time | t_f | | | 9 | | ns |